

# Material Safety Data Sheet

0552HDX, 0554HDX – HDX Wall Patch w/ Primer  
Lightweight Spackling – Acrylic – White – Square  
Tub – Low VOC

MSDS No. 0038P&P – HDX  
Label

Emergency Phone No.  
800-535-5053 - INFOTRAC

## SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION

PRODUCT NAME	Home Depot HDX Wall Patch w/ Primer Lightweight Spackling - ½ Pint & Quart Square Tub - White
MANUFACTURER'S NAME & TELEPHONE NUMBER	Home Depot, Inc. 770-433-8211
STREET ADDRESS	2455 Paces Ferry Road
CITY / STATE / ZIP	Atlanta, Georgia 30339

## SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS

	%	TLV	PEL	UNITS
<b>PRODUCT CONSISTS OF:</b>				
Acrylic Emulsion (mixture)	< 55	NE	NE	
Glass Microspheres ** (65997-17-3), Ceramic Filler ** (66402-68-4) Blend ***	< 15	NE	NE	
Ground Mica ** (12001-26-2) ***	< 10	3	20	mg/m3
Calcium Carbonate ** (1317-65-3) ***	< 10	10	15	mg/m3
Propylene Glycol (57-55-6)	< 2	400****	NE	ppm
Titanium Dioxide ** (13463-67-7) ***	< 2	10	10	mg/m3
Non-hazardous ingredients *	< 10	NA	NA	

\*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). \*\* Inhalation not likely due to products physical state. \*\*\* Wear appropriate dust mask if material sanded. \*\*\*\* TWA. Calculated VOC: < 0.5%/wt, < 10 g/L. CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)

## SECTION 3 – HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF ENTRY	<input checked="" type="checkbox"/> Skin Contact	<input checked="" type="checkbox"/> Skin Absorption	<input checked="" type="checkbox"/> Eye Contact	<input checked="" type="checkbox"/> Inhalation	<input checked="" type="checkbox"/> Ingestion
EMERGENCY OVERVIEW	White colored paste, mild odor. Removal of this product after use may result in the generation of dust. If dry-sanded, exposure to dust may result in material getting into eyes, ears, nose & mouth which may result in irritation.				
EFFECTS OF OVEREXPOSURE	May cause eye, skin, nose, throat & respiratory tract irritation. Harmful if swallowed. Inhalation of dust may result in pulmonary & respiratory damages. Prolonged or repeated exposure to dust may cause lung damage.				
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	Asthma & asthma-like conditions may worsen from prolonged or repeated exposure.				

## SECTION 4 – FIRST AID MEASURES

SKIN CONTACT	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
INGESTION	DO NOT INDUCE VOMITING. Get immediate medical attention.

## SECTION 5 – FIRE FIGHTING MEASURES

<b>FLAMABLE</b>	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
<b>EXTINGUISHING MEDIA</b>	Carbon Dioxide, Dry Chemical, Foam		
<b>FLASHPOINT (°F) &amp; METHOD</b>	>200F (Closed Cup)	<b>UPPER EXPLOSIVE LIMIT (% BY VOLUME)</b>	NE
<b>LOWER EXPLOSIVE LIMIT (% BY VOLUME)</b>	NE	<b>AUTOIGNITION TEMPERATURE (°F)</b>	NE
<b>UNUSUAL FIRE &amp; EXPLOSION HAZARDS</b>	None known.		
<b>SPECIAL FIREFIGHTING PROCEDURES</b>	Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.		

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

<b>PROCEDURES</b>	Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.		
-------------------	---	--	--

## SECTION 7 – HANDLING & STORAGE

<b>HANDLING PROCEDURES &amp; EQUIPMENT</b>	Keep out of reach of children & pets. Do not take internally. Do not breathe vapors or inhale dusts of this product, if sanded. Avoid contact w/ skin & eyes. Do not get on clothing. Use w/ adequate ventilation. Ensure fresh air during application & drying by opening windows & doors.		
<b>STORAGE REQUIREMENTS</b>	Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.		

## SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

<b>RESPIRATORY</b>	In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits. Wear appropriate dust respirator if material is to be dry sanded.		
<b>EYEWEAR</b>	Goggles or safety glasses w/ side shields.		
<b>CLOTHING / GLOVES</b>	Gloves recommended for prolonged or repeated skin contact.		
<b>HYGENIC PRACTICES</b>	Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.		

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>PHYSICAL STATE</b>	Paste	<b>ODOR &amp; APPEARANCE</b>	Mild odor. White paste
<b>SPECIFIC GRAVITY</b>	Approximately 0.25 to 0.75	<b>VAPOR DENSITY (AIR=1)</b>	Heavier than air
<b>EVAPORATION RATE</b>	NE	<b>BOILING POINT (°F)</b>	~ 212 F
<b>pH</b>	7 to 10	<b>SOLUBILITY IN WATER</b>	Soluble.
<b>VAPOR PRESSURE (MM Hg)</b>	NE	<b>%/WT VOLATILE (TNV)</b>	35 to 45%

## SECTION 10 – STABILITY AND REACTIVITY

<b>STABILITY</b>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Stable under normal conditions. Protect from temperature extremes.	
<b>INCOMPATIBILITY</b>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Incompatible w/ strong oxidizers & caustics.	
<b>CONDITIONS TO AVOID</b>	Excessive heat & freezing.		
<b>HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS</b>	Hazardous polymerization will not occur under normal conditions. Carbon Monoxide, Carbon Dioxide & Oxides of Hydrogen may be present during combustion.		

## SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY

ACGIH	Trace residual Formaldehyde present in base emulsion is a suspected human carcinogen. Silica, crystalline present in calcium carbonate filler, a suspected human carcinogen.
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.
IARC	Trace residual Formaldehyde: Human carcinogen. Silica, crystalline present in calcium carbonate filler, classed as a human carcinogen.
NTP	Trace residual Formaldehyde listed as an anticipated carcinogen. Silica, crystalline present in calcium carbonate filler, classed as a known carcinogen.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace residual Formaldehyde from base acrylic emulsion, listed by OSHA & NTP as a potential carcinogen. Crystalline Silica (present in low levels in Calcium Carbonate filler) known to the State of California to cause cancer. Contains Ground Mica, known by the State of California to cause cancer. Contains Titanium Dioxide, a potential carcinogen.

## SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY	Not known or expected w/ normal use.
------------------	--------------------------------------

## SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Local regulations.
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.

## SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION	Product not regulated by DOT. DOT Proper Shipping Name: None. DOT Haz. Class: NA. Packing Group: NA. Haz. Subclass: NA. DOT UN/NA No. NA
------------------------------	--

## SECTION 15 – REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY	Immediate Health Hazard, Chronic Health Hazard.	U.S. STATE REGS	See Section 16.
SARA 313	None known.	TSCA	All ingredients either on TSCA Inventory or exempt. Product contains nothing subject to TSCA 12(B) if exported from U.S.

## SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

Prop 65 Ingredients (Known to State of California to cause cancer): Formaldehyde, various monomers used in polymerization of base emulsion, Mica, Silica Crystalline (present in Calcium Carbonate filler @ low levels). NJ Right-to-Know: (Top 5 Ingredients): Base Acrylic Emulsion (mixture), Water (7732-18-5), Calcium Carbonate (1317-65-3), Soda Lime Borosilicate (Glass Bubbles) (65997-17-3), Mica (12001-26-2). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). Ingredients Known to State of California to cause cancer &/or developmental toxicity &/or reproductive toxicity: Acrylonitrile (107-13-1), Ethyl Acrylate (140-88-5), Formaldehyde (50-00-0). Canadian WHMIS Class: Not regulated. HMIS Ratings: Health: 1, Flammability: 0, Reactivity: 0. Personal Protection: X. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Product contains no Ethylene Glycol, Phthalates, Asbestos or Solvents. INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

**LEGEND:** NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: <u> Larry G. Brandon </u>	<u> VP Technology &amp; General Manager </u>	<u> June 25, 2013 </u>
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.